

Form PTO-1390
(Rev. 12-29-99)

US DEPARTMENT OF COMMERCE PATENT AND TRADEMARK OFFICE

ATTORNEY'S DOCKET NO.

H 3243 PCT/US**TRANSMITTAL LETTER TO THE UNITED STATES
DESIGNATED/ELECTED OFFICE (DO/EO/US)
CONCERNING A FILING UNDER 35 U.S.C. 371**

U.S. APPLICATION NO. (if known see 37 CFR 1.55)

09/857635INTERNATIONAL APPLICATION NO.
PCT/EP99/09404INTERNATIONAL FILING DATE
December 2, 1999PRIORITY DATE CLAIMED
December 9, 1998

TITLE OF INVENTION

**AGENT AND METHOD FOR SEALING OR CONSOLIDATING ROCK, LOOSE ROCK OR SOILS,
ESPECIALLY BORE HOLES**

APPLICANT(S) FOR DO/EO/US

Ilona Lange, Wolfgang Breuer, Claus-Peter Herold, Stephan Von Tapavicza and Dark Mill

Applicant herewith submits to the United States Designated/Elected Office (EO/DO/US) the following items and other information:

1. ☒ This is a **FIRST** submission of items concerning a filing under 35 U.S.C. 371.
2. ☐ This is a **SECOND** or **SUBSEQUENT** submission of items concerning a filing under 35 U.S.C. 371.
3. ☐ This express request to begin national examination procedures (35 U.S.C. 371(f)) at any time rather than delay examination until the expiration of the applicable time limit set in 35 U.S.C. 371(b) and PCT Articles 22 and 39 (1).
4. ☒ A proper Demand for International Preliminary Examination was made by the 19th month from the earliest claimed priority date.
5. ☒ A copy of the International Application as filed (35 U.S.C. 371(c)(2)).
 - a. ☐ is transmitted herewith (required only if not transmitted by the International Bureau).
 - b. ☒ has been transmitted by the International Bureau.
 - c. ☐ is not required, as the application was filed in the United States Receiving Office (RO/US).
6. ☒ A translation of the International Application into English (35 U.S.C. 371(c)(2)).
7. ☒ Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371(c)(3))
 - a. ☐ are transmitted herewith (required only if not transmitted by the International Bureau).
 - b. ☐ have been transmitted by the International Bureau.
 - c. ☐ have not been made; however, the time limit for making such amendments has NOT expired.
 - d. ☒ have not been made and will not be made.
8. ☐ A translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)).
9. ☒ An oath or declaration of the inventor(s) (35 U.S.C. 371(c)(4)). **(UNEXECUTED)**
10. ☐ A translation of the annexes to the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371(c)(5)).

Items 11. to 16. below concern other document(s) or information included:

11. ☐ An Information Disclosure Statement under 37 CFR 1.97 and 1.98.
12. ☐ An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included.
13. ☒ A **FIRST** preliminary amendment
☐ A **SECOND** or **SUBSEQUENT** preliminary amendment.
14. ☐ A substitute specification.
15. ☐ A change of power of attorney and/or address letter.
16. ☐ Other items or information:

**"Express Mail Post Office to Addressee" service Mailing Label Number
EL541613749US**

U.S. Application No. (If known, see 37 CFR 1.535) 02/837635	INTERNATIONAL APPLICATION NO. PCT/EP99/09404	ATTORNEY'S DOCKET NUMBER H 3243 PCT/US					
17. ■ The following fees are submitted: BASIC NATIONAL FEE (37 CFR 1.492(a)(1)-(5)): Neither international preliminary examination fee (37 CFR 1.482) nor international search fee (37 CFR 1.445(a)(2)) paid to USPTO and International Search Report not prepared by the EPO or JPO..... \$1,000.00 International preliminary examination fee (37 CFR 1.482) not paid to USPTO but International Search Report prepared by the EPO or JPO..... \$860.00 International preliminary examination fee (37 CFR 1.482) not paid to USPTO but international search fee (37 CFR 1.445(a)(2)) paid to USPTO \$710.00 International preliminary examination fee paid to USPTO (37 CFR 1.482) but all claims did not satisfy provisions of PCT Article 33(1)-(4) \$690.00 International preliminary examination fee paid to USPTO (37 CFR 1.482) and all claims satisfied provisions of PCT Article 33(1)-(4)..... \$100.00 <div style="text-align: right;">ENTER APPROPRIATE BASIC FEE AMOUNT =</div>		<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th style="width: 60%;">CALCULATIONS</th> <th style="width: 40%;">PTO USE ONLY</th> </tr> <tr> <td style="height: 100px; vertical-align: bottom;"> <div style="text-align: right;">\$ 860</div> </td> <td></td> </tr> </table>		CALCULATIONS	PTO USE ONLY	<div style="text-align: right;">\$ 860</div>	
CALCULATIONS	PTO USE ONLY						
<div style="text-align: right;">\$ 860</div>							
Surcharge of \$130.00 for furnishing the oath or declaration later than <input type="checkbox"/> 20 <input type="checkbox"/> 30 months from the earliest claimed priority date 37 (CFR 1.492(e)).		<div style="text-align: right;">\$ 0</div>					
CLAIMS	NUMBER FILED	NUMBER EXTRA	RATE				
Total Claims	22 - 20 =	2	2 X \$18.00				
Independent Claims	3 - 3 =	0	0 X \$80.00				
Multiple dependent claims (s)(if applicable) 0		+ \$270.00					
TOTAL OF ABOVE CALCULATIONS =		\$ 896					
Reduction of 1/2 for filing by small entity, if applicable. A Small Entity Statement must also be filed. (Note 37 CFR 1.9, 1.27, 1.28).		\$ 0					
SUBTOTAL =		\$ 896					
Processing fee of \$130.00 for furnishing the English translation later the <input type="checkbox"/> 20 <input type="checkbox"/> 30 months from the earliest claimed priority date (37 CFR 1.492(f)).		\$ 0					
TOTAL NATIONAL FEE =		\$ 896					
Fee for recording the enclosed assignment (37 CFR 1.21(h)). The assignment must be accompanied by an appropriate cover sheet (37 CFR 3.28, 3.31). \$40.00 per property		\$ 0					
TOTAL FEES ENCLOSED =		\$ 896					
		Amount to be: refunded:	\$-----				
		charged:	\$896.00				

a. ☐ A check in the amount of \$_____ to cover the above fees is enclosed.

b. ■ Please charge my Deposit Account No. 50-1177 in the amount of \$896.00 to cover the above fees.
 A triplicate copy of this sheet is enclosed. Order No. 01-0341.

c. ■ The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any
 overpayment to Deposit Account No. 50-1177. A triplicate copy of this sheet is enclosed.

**NOTE: Where an appropriate time limit under 37 CFR 1.494 or 1.495 has not been met, a petition to revive (37 CFR 1.137 (a) or (b))
 must be filed and granted to restore the application to pending status.**

SEND ALL CORRESPONDENCE TO: Cognis Corporation, Law Dept.
 2500 Renaissance Blvd., Suite 200
 Gulph Mills, PA 19406

SIGNATURE:

Aaron R. Ettelman
 NAME ATTORNEY FOR APPLICANT
42,516
 REGISTRATION NUMBER

"Express Mail " Mailing Label Number EL541613749US .

PATENT
Docket No. H 3243 PCT/US

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

RE: PCT/EP99/09404
International Filing Date: December 2, 1999
Priority Date Claimed: December 9, 1998
Applicant: Lange, et al.
Title: AGENT AND METHOD FOR SEALING OR CONSOLIDATING ROCK,
LOOSE ROCK OR SOILS, ESPECIALLY BORE HOLES
Applicants' Reference: H 3243 PCT/US

PRELIMINARY AMENDMENT

Commissioner for Patents
Box PCT
Washington, DC 20231

ATTN: DO/EO/US

Prior to the calculation of fees and examination of the above-identified national stage application pursuant to the accompanying submission under 35 U.S.C. §371, please amend the English translation of the International Application submitted herewith, without prejudice, as follows:

In the Specification:

Please amend the instant Specification, without prejudice, as follows:

Please delete all text above line 4 of page 1, and replace the deleted matter with the following new section headings and title of the invention:

--TITLE OF THE INVENTION

Rock and Soil Sealing Compositions Containing Silica Sols
and Hardness Stabilizers, and Methods of Using the Same

BACKGROUND OF THE INVENTION--

At page 3, between lines 2 and 3 thereof, please insert the following new section heading and new paragraph:

**Preliminary Amendment of U.S. National Stage for International Application
PCT/EP99/09404 filed December 2, 1999**

--BRIEF SUMMARY OF THE INVENTION

The present invention relates, in general, to compositions and processes for sealing or consolidating rock, mantle rock or soils and to the use for this purpose of silica sols containing hardness stabilizers.--

At page 3, between lines 19 and 20 thereof, please insert the following new section heading:

--DETAILED DESCRIPTION OF THE INVENTION--

At page 10, before line 1, please add the following new paragraph:

--What is claimed is:--.

On a separate, new page 12, following page 11, please add the following new section heading and paragraph containing an Abstract of the Disclosure:

--ABSTRACT OF THE DISCLOSURE

Compositions which comprise an aqueous silica sol and one or more hardness stabilizers selected from inorganic polyphosphates, phosphonic acids, aminoethylene phosphonic acids, phosphoric acid esters, phosphonocarboxylic acids, and polycarboxylics, are described for sealing and/or consolidating rocks and/or soils, particularly in digging or drilling applications. Methods of sealing and/or consolidating rocks and soils using said compositions are also described. --

In the Claims:

Please add new claims 11-32, as follows:

--11. (New) A composition comprising:

(a) an aqueous silica sol, wherein the composition contains SiO_2 in an amount of from 2 to 40% by weight based upon the weight of the composition; and

**Preliminary Amendment of U.S. National Stage for International Application
PCT/EP99/09404 filed December 2, 1999**

(b) from 0.01 to 400 ppm of a hardness stabilizer selected from the group consisting of inorganic polyphosphates, phosphonic acids, aminoethylene phosphonic acids, phosphoric acid esters, phosphonocarboxylic acids, polycarboxylics, and mixtures thereof.--

--12. (New) The composition according to claim 11, wherein the aqueous silica sol comprises amorphous silica having an average particle size of from 1 to 150 nm and a specific surface value of from 50 to 700 m²/g.--

--13. (New) The composition according to claim 11, wherein the aqueous silica sol comprises amorphous silica having an average particle size of from 5 to 70 nm and a specific surface value of from 50 to 700 m²/g.--

--14. (New) The composition according to claim 11, wherein the aqueous silica sol comprises amorphous silica particles having surface-stabilizing hydroxyl groups.--

--15. (New) The composition according to claim 12, wherein the aqueous silica sol comprises amorphous silica particles having surface-stabilizing hydroxyl groups.--

--16. (New) The composition according to claim 11, wherein the hardness stabilizer is selected from the group consisting of aminotris(methylenephosphonic acid), 1-hydroxyethane-1,1-diphosphonic acid, phosphonobutane tricarboxylic acid, polyacrylic acid and mixtures thereof.--

--17. (New) The composition according to claim 11, wherein the hardness stabilizer is present in an amount of from 0.1 to 200 ppm.--

--18. (New) The composition according to claim 11, wherein the hardness stabilizer is present in an amount of from 1 to 100 ppm.--

**Preliminary Amendment of U.S. National Stage for International Application
PCT/EP99/09404 filed December 2, 1999**

--19. (New) The composition according to claim 12, wherein the hardness stabilizer is selected from the group consisting of aminotris(methylenephosphonic acid), 1-hydroxyethane-1,1-diphosphonic acid, phosphonobutane tricarboxylic acid, polyacrylic acid and mixtures thereof.--

--20. (New) The composition according to claim 12, wherein the hardness stabilizer is present in an amount of from 0.1 to 200 ppm.--

--21. (New) A method of sealing and/or consolidating loose and/or permeable materials, said method comprising:

(a) providing a material to be treated selected from the group consisting of rocks, mantle rock, soils, and mixtures thereof;

(b) contacting the material with an aqueous silica sol; and

(c) contacting the material with a hardness stabilizer selected from the group consisting of inorganic polyphosphates, phosphonic acids, aminoethylene phosphonic acids, phosphoric acid esters, phosphonocarboxylic acids, polycarboxylics, and mixtures thereof.--

--22. (New) The method according to claim 21, wherein the material is contacted with the aqueous silica sol and the hardness stabilizer simultaneously in the form of a water-based composition comprising both the aqueous silica sol and the hardness stabilizer.--

--23. (New) The method according to claim 21, wherein the material is contacted with the aqueous silica sol, and subsequently contacted with the hardness stabilizer by adding the hardness stabilizer to the aqueous silica sol.--

--24. (New) The method according to claim 21, wherein the aqueous silica sol comprises amorphous silica having an average particle size of from 1 to 150 nm and a specific surface value of from 50 to 700 m²/g.--

**Preliminary Amendment of U.S. National Stage for International Application
PCT/EP99/09404 filed December 2, 1999**

--25. (New) The method according to claim 21, wherein the aqueous silica sol comprises amorphous silica having an average particle size of from 5 to 70 nm and a specific surface value of from 50 to 700 m²/g.--

--26. (New) The method according to claim 21, wherein the aqueous silica sol comprises amorphous silica particles having surface-stabilizing hydroxyl groups.--

--27. (New) The method according to claim 21, wherein the hardness stabilizer is selected from the group consisting of aminotris(methylenephosphonic acid), 1-hydroxyethane-1,1-diphosphonic acid, phosphonobutane tricarboxylic acid, polyacrylic acid and mixtures thereof.--

--28. (New) The method according to claim 22, wherein the hardness stabilizer is present in the composition in an amount of from 0.01 to 400 ppm.--

--29. (New) The method according to claim 23, wherein the hardness stabilizer is added to the aqueous silica sol such that the hardness stabilizer is present in the sol in an amount of from 0.01 to 400 ppm.--

--30. (New) The method according to claim 22, wherein the hardness stabilizer is present in the composition in an amount of from 0.1 to 200 ppm.--

--31. (New) The method according to claim 23, wherein the hardness stabilizer is added to the aqueous silica sol such that the hardness stabilizer is present in the sol in an amount of from 0.1 to 200 ppm.--

--32. (New) A method of sealing and/or consolidating loose and/or permeable materials, said method comprising:

(a) providing a material to be treated selected from the group consisting

Variable	Mean		SD		t		p	
	Control	Case	Control	Case	Control	Case	Control	Case
Age	30.5	30.5	1.2	1.2	0.0	0.0	0.999	0.999
Gender	1.0	1.0	0.0	0.0	0.0	0.0	0.999	0.999
Education	12.0	12.0	1.0	1.0	0.0	0.0	0.999	0.999
Income	1.0	1.0	0.0	0.0	0.0	0.0	0.999	0.999
Marital status	1.0	1.0	0.0	0.0	0.0	0.0	0.999	0.999
Occupation	1.0	1.0	0.0	0.0	0.0	0.0	0.999	0.999
Religion	1.0	1.0	0.0	0.0	0.0	0.0	0.999	0.999
Health status	1.0	1.0	0.0	0.0	0.0	0.0	0.999	0.999
Family size	1.0	1.0	0.0	0.0	0.0	0.0	0.999	0.999
Urban/rural	1.0	1.0	0.0	0.0	0.0	0.0	0.999	0.999
Time of day	1.0	1.0	0.0	0.0	0.0	0.0	0.999	0.999
Season	1.0	1.0	0.0	0.0	0.0	0.0	0.999	0.999
Weather	1.0	1.0	0.0	0.0	0.0	0.0	0.999	0.999
Time of day	1.0	1.0	0.0	0.0	0.0	0.0	0.999	0.999
Season	1.0	1.0	0.0	0.0	0.0	0.0	0.999	0.999
Weather	1.0	1.0	0.0	0.0	0.0	0.0	0.999	0.999
Time of day	1.0	1.0	0.0	0.0	0.0	0.0	0.999	0.999
Season	1.0	1.0	0.0	0.0	0.0	0.0	0.999	0.999
Weather	1.0	1.0	0.0	0.0	0.0	0.0	0.999	0.999
Time of day	1.0	1.0	0.0	0.0	0.0	0.0	0.999	0.999
Season	1.0	1.0	0.0	0.0	0.0	0.0	0.999	0.999
Weather	1.0	1.0	0.0	0.0	0.0	0.0	0.999	0.999
Time of day	1.0	1.0	0.0	0.0	0.0	0.0	0.999	0.999
Season	1.0	1.0	0.0	0.0	0.0	0.0	0.999	0.999
Weather	1.0	1.0	0.0	0.0	0.0	0.0	0.999	0.999
Time of day	1.0	1.0	0.0	0.0	0.0	0.0	0.999	0.999
Season	1.0	1.0	0.0	0.0	0.0	0.0	0.999	0.999
Weather	1.0	1.0	0.0	0.0	0.0	0.0	0.999	0.999
Time of day	1.0	1.0	0.0	0.0	0.0	0.0	0.999	0.999
Season	1.0	1.0	0.0	0.0	0.0	0.0	0.999	0.999
Weather	1.0	1.0	0.0	0.0	0.0	0.0	0.999	0.999
Time of day	1.0	1.0	0.0	0.0	0.0	0.0	0.999	0.999
Season	1.0	1.0	0.0	0.0	0.0	0.0	0.999	0.999
Weather	1.0	1.0	0.0	0.0	0.0	0.0	0.999	0.999
Time of day	1.0	1.0	0.0	0.0	0.0	0.0	0.999	0.999
Season	1.0	1.0	0.0	0.0	0.0	0.0	0.999	0.999
Weather	1.0	1.0	0.0	0.0	0.0	0.0	0.999	0.999
Time of day	1.0	1.0	0.0	0.0	0.0	0.0	0.999	0.999
Season	1.0	1.0	0.0	0.0	0.0	0.0	0.999	0.999
Weather	1.0	1.0	0.0	0.0	0.0	0.0	0.999	0.999
Time of day	1.0	1.0	0.0	0.0	0.0	0.0	0.999	0.999
Season	1.0	1.0	0.0	0.0	0.0	0.0	0.999	0.999
Weather	1.0	1.0	0.0	0.0	0.0	0.0	0.999	0.999
Time of day	1.0	1.0	0.0	0.0	0.0			

(b) contacting the material with a composition comprising: (i) an aqueous silica sol, wherein the composition contains SiO₂ in an amount of from 2 to 40% by weight based upon the weight of the composition; and (ii) from 0.1 to 200 ppm of a hardness stabilizer selected from the group consisting of aminotris(methylenephosphonic acid), 1-hydroxyethane-1,1-diphosphonic acid, phosphonobutane tricarboxylic acid, polyacrylic acid and mixtures thereof.--

6

**Preliminary Amendment of U.S. National Stage for International Application
PCT/EP99/09404 filed December 2, 1999**

REMARKS

Claims 11-32 are currently pending in the instant application.

The Specification has been amended to delete the original section headings and to insert the preferred section headings pursuant to 37 C.F.R. §1.77. A new Title of the Invention has been inserted. An Abstract of the Disclosure, in accordance with the disclosure, has been added. It is submitted that the amendments to the Specification made herein introduce no new matter. All of the amendments to the Specification constitute deletions of original section headings and/or paragraphs, and insertions or additions of new section headings and/or paragraphs. Accordingly, pursuant to 37 C.F.R. §1.121(b)(1)(iii), no separate page captioned "VERSION WITH MARKINGS TO SHOW CHANGES MADE" is necessary. A separate page containing a clean copy of the Abstract of the Disclosure has been attached for the Examiner's convenience. Entry of the amendments to the Specification made herein are therefore proper and respectfully requested.

Original claims 1-10 have been canceled and replaced with new claims 11-32 solely for the purpose of improving clarity and grammar, which may suffer in translation, and not for any reason which relates to the statutory requirements for a patent. New claims 11-32 have not been added in response to any rejection, nor in anticipation of any rejection. Applicants respectfully submit that the scope of new claims 11-32 generally corresponds to the scope of original claims 1-10, and that new claims 11-32 are no narrower than original claims 1-10. Furthermore, although a moot point in view of their cancellation, Applicants respectfully submit that original claims 1-10 satisfied the requirements of 35 U.S.C. §112, as filed. New claims 11-32 are supported by the claims as originally filed and in the Specification, for example, at page 3, lines 5-13; at page 3, lines 20-29; at page 5, lines 10-16; and in the Examples. No new matter has been introduced. All of the amendments to the Claims constitute cancellation of original claims and the addition of new claims. Accordingly, pursuant to 37 C.F.R. §1.121(c)(1)(ii), no separate page captioned "VERSION WITH MARKINGS TO SHOW CHANGES MADE" is necessary. Entry is therefore proper and respectfully requested.

**Preliminary Amendment of U.S. National Stage for International Application
PCT/EP99/09404 filed December 2, 1999**

Prompt examination of the instant application in view of the amendments made
herein is respectfully requested.

Respectfully submitted,

ILONA LANGE, et al.

June 7, 2001
(Date)

AARON R. ETTELMAN

(Reg. No. 42,516)

Attorney for Applicants

Telephone: (610) 278-4930

Facsimile: (610) 278-6548

E-Mail: AARON.ETTELMAN@HENKEL-AMERICAS.COM

Cognis Corporation, Patent Dept.
2500 Renaissance Blvd., Suite 200
Gulph Mills, PA 19406

ARE/ras

G:\Data\amend\H3243.pam.doc

**Agent and Method for Sealing or Consolidating Rock, Loose Rock or
Soils, Especially Boreholes**

This invention relates to a composition and a process for sealing or consolidating rock, mantle rock or soils and to the use for this purpose of certain silica sols containing hardness stabilizers.

The consolidation or sealing of rock, mantle rock or soils is a
5 measure regularly necessary in construction engineering, for example for underpinning buildings, for sealing building pits or tips, in tunnel and canal construction and, above all, in geological exploration, such as the drilling of oil or natural gas pools. In the last of these applications, the sealing of wells is particularly important. Wells are sunk into the ground until a
10 formation carrying oil, gas or - in well construction - water is reached. The well is stabilized against the formation by a cement casing. This cement casing is broken open at the bottom of the well so that the material to be brought up is able to pass freely from the formation into the well. Besides oil or gas, however, water also enters the well and has to be removed from
15 the oil/gas by elaborate processes. Accordingly, efforts are made to minimize or avoid the penetration of water, so that the water-carrying parts of the formation are sealed off by suitable binders. However, consolidation or sealing is also a standard measure in the protection of agricultural land against wind or water erosion.

20 In general, binders, such as cement, bitumen, calcium salts or waterglass, are used in construction engineering. However, cement has the disadvantage that the particles are often not small enough to be able to penetrate into fine cracks or pores, resulting in an unsatisfactory sealing or consolidating effect. Even the use of waterglasses (an aqueous solution of
25 sodium silicate) or microsilicas (an aqueous dispersion of amorphous silicon dioxide) does not always produce the required sealing effect. Accordingly, **EP 530 600** proposes the use of silica sols for sealing or

consolidation. Silica sols are colloidal solutions of amorphous silicon dioxide which has a particle size of 7 to 50 nm. These silica sols gel in the presence of certain electrolytes or in the event of changes in the pH of the aqueous sols. By crosslinking of the SiO_2 units, the gel becomes more viscous until consolidation is complete. Electrolytes which initiate gelation are generally present in the material to be consolidated or sealed. They are preferably salts of aluminium, iron, calcium or magnesium. However, EP 0 530 600 A1 proposes using silica sols in combination with a calcium donor in order to achieve rapid conversion of the sol into the gel.

Now, applicants have found that, surprisingly, the use of silica sols does not always lead to the required sealing or consolidating effects. This is particularly the case in the sealing of wells against penetrating formation water. According to applicants' observations, a free water phase frequently occurs which is a sign that no gelation and hence no sealing has taken place. Accordingly, without being confined to one particular theory, applicants assume that, in contrast to the teaching of EP 0 530 600 A1, the formation of alkaline earth metal silicates and, above all, calcium silicate can inhibit the gelation process. Accordingly, one of the problems addressed by the present invention was to provide a sealing or consolidating process which could even be carried out in the presence of water containing alkaline earth metal ions.

In addition, it is often not desirable in the sealing of wells to achieve rapid solidification of the binder. The binder is transported under pressure to the bottom of the well through a suitable pipe and is forced into the formation there. The effect of rapid solidification of the binder would be that the binder would also gel in the pipe itself which of course is not what is wanted. On the contrary, the gelling effect should be delayed to the extent that the entire binder is forced into the formation by flushing, for example with water, so that gelation and consolidation only occur in the required places. Accordingly, another problem addressed by the present invention

was to provide a process for the delayed consolidation or sealing of rock, mantle rock or soils.

It has now surprisingly been found that a mixture of aqueous silica sol and certain inhibitors for Ca^{2+} ions solves the problems stated above.

5 In a first embodiment, the present invention relates to a water-based composition for sealing or consolidating rock, mantle rock or soils in contact with water containing Ca^{2+} ions, the composition containing 2 to 40% by weight of SiO_2 (dry matter, based on the composition) in the form of an aqueous silica sol and, in addition, hardness stabilizers from the class of
10 inorganic polyphosphates, phosphonic acids, aminoethylene phosphonic acids, phosphoric acid esters, phosphonocarboxylic acids and polycarboxylic acids or mixtures of these substances in concentrations of 0.01 to 400 ppm.

The compositions according to the invention are generally suitable
15 both for the consolidation and for the sealing of any type of rock, mantle rock or soils in contact with water containing Ca^{2+} ions. Typical applications include construction engineering, particularly tunnel and well construction, and geological exploration, more particularly the sealing of wells, more precisely their walls, against penetrating formation water.

20 Besides water, the compositions according to the invention contain silica sols containing amorphous SiO_2 in quantities of 2 to 60% by weight, expressed as dry matter and based on the sol, as carrier liquid. However, silica sols containing 25 to 50% by weight amorphous SiO_2 are preferred for the compositions according to the invention. The amorphous SiO_2 is
25 present in the form of non-interlinked spherical individual particles surface-stabilized by hydroxyl groups. The average particle diameter is in the range from 1 to 150 nm, preferably in the range from 5 to 70 nm and more particularly in the range from 5 to 40 nm. The specific surface of the silica sols is in the range from 50 to 700 m^2/g , as measured by the BET method.
30 By virtue of the colloidal distribution of the particles, no sedimentation of

particles is observed with silica sols. Accordingly, the sols may be stored for years. Aqueous silica sols are generally used. However, amorphous SiO_2 may also be converted into sols in other solvents, for example acetone or short-chain organic alcohols, such as methanol, ethanol or propanol (cf. **Ullmanns Encyklopädie der Technischen Chemie, 4th Edition, Vol. 21, pages 456 to 463, Weinheim 1982**). However, the compositions according to the invention contain only aqueous silica sols.

The compositions according to the invention contain in all, i.e. including the water content of the silica sols, between 60 and 98% by weight and more particularly between 60 and 80% by weight of water which preferably contains only small amounts of electrolytes, for example between 0.001 and 0.1% by weight. The water is preferably free from electrolytes. Electrolytes in the present context are understood in particular to be cations of mono- and divalent alkali metal and alkaline earth metal ions, i.e. Na^+ , K^+ , Ca^+ and Mg^{2+} ions. Aqueous silica sols of the type described above are present in the compositions in quantities of 20 to 60% by weight. According to the invention, so-called hardness stabilizers are added to the mixture of silica sol and water in concentrations of 0.01 to 400 ppm. Hardness stabilizers are compounds which, in less than stoichiometric quantities known for the purpose, are capable of completely and permanently preventing the precipitation of hardness ions from supersaturated aqueous solutions. To this extent, it was surprising that the addition of these compounds only leads to delayed gelation of the silica sols but does not permanently suppress their gelation. Hardness ions are mainly alkaline earth metal ions, more particularly calcium and magnesium ions (threshold effect). Particulars can be found in **Römpps Chemie Lexikon, 9th Edition, Vol. 6, 1994, pages 5000 to 5002**.

The compositions according to the invention contain compounds from the class of inorganic polyphosphates, phosphonic acid, aminoethylene phosphonic acids, phosphoric acid esters,

phosphonocarboxylic acids and polycarboxylic acids or mixtures thereof as hardness stabilizers. Salts of these compounds are also suitable. Compositions containing hardness stabilizers from the group consisting of aminotris(methylenephosphonic acid), 1-hydroxyethane-1,1-diphosphonic acid, phosphonobutane tricarboxylic acid, polyacrylic acid, polyaspartic acid, polymaleic acid or derivatives thereof or mixtures of these compounds are particularly preferred. Compositions containing tetrakis-[(phosphonomethyl)-imino]-bis-[2,1-ethanediylnitrido-bis-methylene]-phosphonic acid and/or salts thereof as hardness stabilizers are most particularly preferred.

Preferred mixtures of these stabilizers contain, for example, 1-hydroxyethane-1,1-diphosphonic acid sodium salt and polyacrylic acid or 1-hydroxyethane-1,1-diphosphonic acid sodium salt, aminotris(methylenephosphonic acid) and polyacrylic acid. The concentration in which the hardness stabilizers are used is between 0.01 and 400 ppm, more particularly in the range from 0.1 to 200 ppm and preferably in the range from 1 to 100 ppm, based on hardness stabilizer active substance.

In another embodiment, the present invention relates to a process for sealing or consolidating rock, mantle rock or soils in contact with water containing Ca^{2+} ions, in which the material to be consolidated or sealed is contacted with a solution containing aqueous silica sol and hardness stabilizers from the class of inorganic polyphosphates, phosphonic acids, aminoethylene phosphonic acids, phosphoric acid esters, phosphonocarboxylic acids and polycarboxylic acids or mixtures of these substances.

Aqueous silica sols containing 20 to 60% by weight SiO_2 (dry matter, based on the aqueous sol) are preferably used for this purpose. In general, the composition is forced under pressure into the material to be sealed or consolidated. The hardness stabilizers are then added during or after the treatment with the silica sol. They are preferably used in such quantities that the stabilizer concentration, based on the aqueous silica sol solution, is in the range from 0.01 to 400 ppm, preferably in the range from

0.1 to 200 ppm and more particularly in the range from 1 to 100 ppm.

In one particularly preferred embodiment, the process according to the invention is used for sealing underground formations, more particularly wells. To this end, the silica sol/water/stabilizer mixture is pumped through
5 the feed pipe by suitable pumps to the bottom of the well, such a pressure being applied that the mixture penetrates deeply into the formation. This is followed by flushing with water until the mixture has been completely removed from the pipe. In this connection, the process according to the invention enjoys another advantage because the composition used only
10 gels with a certain delay. Under the temperature, pH and pressure conditions at the bottom of the well, the composition preferably solidifies some 30 to 60 minutes after contacting with the material to be consolidated or sealed and hence with the water containing Ca^{2+} ions. The temperatures at the bottom of the well are normally in the range from 30 to
15 200°C , depending on the depth. The pressure is typically between 10 and 500 bar, again dependent on depth.

The most suitable stabilizer concentration can be selected in dependence upon the concentration of Ca^{2+} ions in the water with which the material to be consolidated or sealed is in contact. It has been found
20 that the hardness stabilizers should preferably be present in the compositions according to the invention in such quantities that, based on a predetermined volume, the ratio by weight of Ca^{2+} ions to the hardness stabilizers is in the range from 0.5 to 5.0:1. The quantity of Ca^{2+} ions may readily be calculated through the determination of the water hardness.

25 The water in contact with the material to be consolidated or sealed generally has a content of Ca^{2+} ions of greater than 2 mmol/l and preferably greater than 4 mmol/l. Typical Ca^{2+} concentrations are in the range from 3 to 8 mmol/l. The pH of the formation water is generally in the acidic to mildly alkaline range, i.e. between 6 and 9. It has been found that
30 reduction in pH to values of 2 to 5 can generally prevent gelation.

Accordingly, the process according to the invention is preferably carried out at pH values of 6 to 9 or the composition according to the invention is preferably formulated by addition of acids or bases in such a way that its pH value is in the range mentioned.

- 5 The present invention also relates to the use of the compositions described in the foregoing for consolidating or sealing rock, mantle rock or soils in contact with water containing Ca^{2+} ions.

Examples

10

The effectiveness of the process according to the invention was determined as follows: 11 g of a silica sol (Köstrosol® 0830 of Chemiewerk Bad Köstritz) were mixed with 40 g of deionized water and hardness stabilizers were subsequently added to the sol in various quantities. Between 0.7 and 1.0 ml of a calcium chloride solution (concentration of Ca^{2+} ions: 28,200 ppm) was then added dropwise to the resulting mixture, followed by heating for 15 minutes to 100°C. The vessel was left standing without stirring to cool. After 30 minutes, the degree of gelation was visually determined.

- 20 The following evaluation was made:

100% solid	++
80 to almost 100% solid	+
less than 80% solid	-

The following hardness stabilizers were tested:

- A: 1-hydroxyethane-1,1-diphosphonic acid
25 B: amino-tris-(methylene phosphonic acid)
C: 1-hydroxyethane-1,1-diphosphonic acid disodium salt
D: mixture of B and C and polyacrylic acid

The stabilizers were used in the form of commercially available aqueous solutions (all products of Henkel KGaA):

- A: 60% by weight active substance (Turpinal® SL)
- B: 50% by weight active substance (Turpinal® D2)
- C: 10% by weight active substance (Turpinal® -2-NZ)
- D: 30% by weight active substance (Fostex® 617 B)

The quantities in Table 1 are based on active substance.

The results of the tests are set out in Table 1.

Table 1

No.	Stabilizer	Stabilizer concentration [ppm]	CaCl ₂ solution [ml]	Ca ²⁺ content in the solution [% by weight]	Ratio by weight Ca ²⁺ :stabilizer	Gelation after 30 mins.
1	A	0.1	0.8	0.04	0.7	++
2	A	0.2	0.8	0.04	1.0	++
3	B	0.3	0.8	0.04	1.4	+
4	B	0.3	0.7	0.04	2.0	++
5	C	0.7	1.0	0.06	1.3	++
6	C	0.7	1.0	0.06	1.5	+
7	D	0.7	1.0	0.06	4.0	++

Tests were also carried out at elevated temperature and pressure in order to simulate the conditions prevailing at the bottom of the well. Quantities of 5 g of a 50% by weight aqueous silica sol were diluted with 45 g of water and a certain ratio by weight of Ca²⁺ to SiO₂ was then adjusted by addition of a CaCl₂ solution (0.04% by weight Ca²⁺). The system was then heated for 30 minutes to 150°C in an autoclave under 10 bar pressure (nitrogen atmosphere) and left under those conditions for two hours. The results of the visual evaluation of the solutions are set out in Table 2.

Table 2

Solution	Ca:SiO ₂ [% by weight]	Effect
8	0.005	Thinly liquid
9	0.010	Slight gelation
10	0.020	Gelation
11	0.030	Gelation

Various quantities of stabilizer D were then added to solution 10 under the described conditions. It was found that the addition of 100 and 200 ppm of stabilizer resulted in delayed gelation after three hours. At higher concentrations, there was no sign of gelation. Accordingly, the process according to the invention leads to a desired delay in the gelation of the silica sol solutions, even at elevated temperature and pressure.

CLAIMS

1. A water-based composition for sealing or consolidating rock, mantle rock or soils in contact with water containing Ca^{2+} ions, the composition containing 2 to 40% by weight of SiO_2 (dry matter, based on the composition) in the form of an aqueous silica sol, characterized in that it
5 contains hardness stabilizers from the class of inorganic polyphosphates, phosphonic acids, aminoethylene phosphonic acids, phosphoric acid esters, phosphonocarboxylic acids and polycarboxylic acids or mixtures of these substances in concentrations of 0.01 to 400 ppm.
2. A composition as claimed in claim 1, characterized in that the
10 hardness stabilizers are selected from the group consisting of aminotris(methylenephosphonic acid), 1-hydroxyethane-1,1-diphosphonic acid, phosphonobutane tricarboxylic acid, polyacrylic acid or mixtures of these compounds.
3. A composition as claimed in claim 1 or 2, characterized in that it
15 contains the hardness stabilizers in concentrations of 0.1 to 200 ppm and preferably in concentrations of 1 to 100 ppm.
4. A process for sealing or consolidating rock, mantle rock or soils in contact with water containing Ca^{2+} ions, in which the material to be consolidated or sealed is contacted with a solution containing aqueous
20 silica sol and hardness stabilizers from the class of inorganic polyphosphates, phosphonic acids, aminoethylene phosphonic acids, phosphoric acid esters, phosphonocarboxylic acids and polycarboxylic acids or mixtures of these substances.
5. A process as claimed in claim 4, characterized in that aqueous silica
25 sols containing 20 to 60% by weight of SiO_2 and preferably 25 to 50% by weight of SiO_2 (dry matter, based on the aqueous sol) are used.
6. A process as claimed in claim 4 or 5, characterized in that the hardness ions are added in such quantities that their concentration in the aqueous silica sol solution is between 0.01 and 400 ppm, preferably

between 0.1 and 200 ppm and more particularly between 1 and 100 ppm.

7. A process as claimed in any of claims 4 to 6, characterized in that the material to be consolidated or sealed is in contact with water having a concentration of Ca^{2+} ions of more than 2 mmol/l

5 8. A process as claimed in any of claims 4 to 7, characterized in that it is used to seal underground formations, preferably wells.

9. A process as claimed in any of claims 4 to 8, characterized in that the consolidating or sealing effect begins 30 to 60 minutes after contacting of the composition with the material to be consolidated or sealed.

10 10. The use of the compositions claimed in any of claims 1 to 3 for sealing or consolidating rock, mantle rock or soils in contact with water containing Ca^{2+} ions.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000

#5

Type a plus sign (+) inside this box → ☐

0010/PTO Rev. 8/95		U.S. Department of Commerce Patent and Trademark Office		Attorney Docket Number	H 3243 PCT/US
DECLARATION FOR UTILITY OR DESIGN PATENT APPLICATION				First Named Inventor	LANGE, Iлона
				COMPLETE IF KNOWN	
				Application Number	09/857,635
				Filing Date	11/09/2001
				Group Art Unit	
				Examiner Name	
<input type="checkbox"/> Declaration Submitted with Initial Filing		OR		<input checked="" type="checkbox"/> Declaration Submitted after Initial Filing	

As a below named inventor, I hereby declare that:

My residence, post office address, and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

**AGENT AND METHOD FOR SEALING OR CONSOLIDATING ROCK, LOOSE ROCK OR SOILS,
ESPECIALLY BORE HOLES**

(Title of the Invention)

the specification of which

☐ is attached hereto

OR

☒ was filed on (MM/DD/YYYY)

12/02/1999

as United States Application Number or PCT International

Application Number

PCT/EP99/09404

and was amended on (MM/DD/YYYY)

(if applicable).

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment specifically referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in Title 37 Code of Federal Regulations, § 1.56.

I hereby claim foreign priority benefits under Title 35, United States Code §119(a)-(d) or §365(b) of any foreign application(s) for patent or inventor's certificate, or §365(a) of any PCT International application which designated at least one country other than the United States of America, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or of any PCT International application having a filing date before that of the application on which priority is claimed.

Prior Foreign Application Number(s)	Country	Foreign Filing Date (MM/DD/YYYY)	Priority Not Claimed	Certified Copy Attached? YES NO
198 56 729.4	DE	12/09/1998	<input type="checkbox"/>	<input type="checkbox"/> <input checked="" type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/>

☐ Additional foreign application numbers are listed on a supplemental priority sheet attached hereto:

I hereby claim the benefit under Title 35, United States Code §119(e) of any United States provisional application(s) listed below.

Application Number(s)	Filing Date (MM/DD/YYYY)	Additional provisional application numbers are listed on a supplemental priority sheet attached hereto.
		<input type="checkbox"/>

Burden Hour Statement: This form is estimated to take .4 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.

"Express Mail Post Office
to Addressee" service
Mailing Label Number
EL541613925US

DECLARATION

Page 2

I hereby claim the benefit under Title 35, United States Code §120 of any United States application(s), or §365(c) of any PCT international application designating the United States of America, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT international application in the manner provided by the first paragraph of Title 35, United States Code §112.1 acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations §1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application.

U.S. Parent Application Number	PCT Parent Number	Parent Filing Date (MM/DD/YYYY)	Parent Patent Number (if applicable)
	PCT/EP99/09404	12/02/1999	

☐ Additional U.S. or PCT international application numbers are listed on a supplemental priority sheet attached hereto.

As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith:

☐ Firm Name Customer Number or label
OR
☒ List Attorney(s) and/or agent(s) name and registration number below:

Name	Registration Number	Name	Registration Number
John E. Drach	<u>32,891</u>	Aaron R. Ettelman	<u>42,516</u>
Steven J. Trzaska	<u>36,296</u>	Henry E. Millson, Jr.	<u>18,980</u>

☐ Additional attorney(s) and/or agent(s) named on a supplemental sheet attached hereto.

Please direct all correspondence to: ☒ Customer Number or label 23657 OR ☒ Fill in correspondence address below

Name	Aaron R. Ettelman		
Address			
Address			
City		State	ZIP
Country	Telephone	610-278-4930	Fax 610-278-6548

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Name of Sole or First Inventor:

☐ A petition has been filed for this unsigned


Given Name	<u>Ilona</u>	Middle Initial		Family Name	<u>LANGE</u>	Suffix e.g. Jr.	
Inventor's Signature	<u>Ilona Lange</u>				Date	<u>10/25/01</u>	
Residence: City	<u>Langenfeld</u>	State	<u>DEX</u>	Country	<u>Germany</u>	Citizenship	<u>Germany</u>
Post Office Address	<u>Nelly-Sachs-Strasse 9</u>						
Post Office Address							
City	<u>40764 Langenfeld</u>	State		Zip		Country	<u>Germany</u>
Applicant Authority							

☒ Additional inventors are being named on supplemental sheet(s) attached hereto


DECLARATION

ADDITIONAL INVENTOR(S)
Supplemental Sheet


2-00

Name of Additional Joint Inventor, if any:										<input type="checkbox"/> A petition has been filed for this unsigned inventor													
Given Name		Wolfgang				Middle Initial				Family Name		BREUER				Suffix e.g. Jr.							
Inventor's Signature										Date		10/25/01											
Residence: City		Korschenbroich				State		DEX		Country		Germany				Citizenship		Germany					
Post Office Address		Clara-Schumannstrasse 13																					
Post Office Address																							
City		41352 Korschenbroich				State				Zip				Country		Germany				Applicant Authority			


3-00

Name of Additional Joint Inventor, if any:										<input type="checkbox"/> A petition has been filed for this unsigned inventor													
Given Name		Claus-Peter				Middle Initial				Family Name		HEROLD				Suffix e.g. Jr.							
Inventor's Signature										Date		10/25/01											
Residence: City		Mettmann				State		DEX		Country		Germany				Citizenship		Germany					
Post Office Address		Ostpreussenstrasse 26																					
Post Office Address																							
City		40822 Mettmann				State				Zip				Country		Germany				Applicant Authority			

4-00

Name of Additional Joint Inventor, if any:										<input type="checkbox"/> A petition has been filed for this unsigned inventor													
Given Name		Stephan				Middle Initial				Family Name		VON TAPAVICZA				Suffix e.g. Jr.							
Inventor's Signature										Date		10/25/01											
Residence: City		Erkrath				State		DEX		Country		Germany				Citizenship		Germany					
Post Office Address		Thomas-Mann-Strasse 12																					
Post Office Address																							
City		40699 Erkrath				State				Zip				Country		Germany				Applicant Authority			

5-00

Name of Additional Joint Inventor, if any:										<input type="checkbox"/> A petition has been filed for this unsigned inventor													
Given Name		Dark				Middle Initial				Family Name		MILL				Suffix e.g. Jr.							
Inventor's Signature										Date		10/25/01											
Residence: City		Neustadt				State		DEX		Country		Germany				Citizenship		Germany					
Post Office Address		In Rahlandsfeld 9																					
Post Office Address																							
City		31535 Neustadt				State				Zip				Country		Germany				Applicant Authority			

☐ Additional inventors are being named on supplemental sheet(s) attached hereto